

AGL UPSTREAM INVESTMENTS PTY LTD ROSALIND PARK GAS PLANT Monthly Continuous Air Monitoring Report

Reporting Period: January 2019

AGL Upstream Investments Pty Ltd ABN 58 115 063 744 Locked Bag 3013, Australia Square, NSW 1215 200 George Street, Sydney NSW 2000

Telephone: 02 9921 2999 Facsimile: 02 9921 2474

Complaints Line (24 hours): 1800 039 600



Foreword

PREMISES Rosalind Park Gas Plant

Lot 35 Medhurst Road GILEAD NSW 2560

LICENCE DETAILS Environment Protection Licence 12003

LICENCEE AGL Upstream Investments Pty Limited

LICENCEE'S ADDRESS Locked Bag 3013, Australia Square, NSW 1215

REPORTING PERIOD 01 January 2019 to 31 January 2019

DATE of MONITORING Continuous

OBTAINED DATA DATE 07 February 2019

REPORT DATE 14 February 2019

REPORT PREPARED BY Aaron Clifton

Environment Business Partner

SUMMARY OF ACTIVITY

Rosalind Park Gas Plant, located approximately 60km south west of Sydney, is a natural gas processing and treatment plant, used to process coal seam natural gas from the Camden Gas Project.

Produced natural gas is cleaned, dehydrated, compressed and odourised before being measured and transported by pipeline about 500 metres into the nearby Moomba to Sydney Natural Gas Pipeline. The premises are covered by Environment Protection Licence 12003 which includes all gas wells, gas gathering, reticulation systems, trunk lines and associated effluent storage areas and work areas of the Camden Gas Project.



This Monitoring Report relates to those air monitoring activities specified in Part 5, Monitoring and Recording Conditions, of Environment Protection Licence (**EPL**) 12003. The Licence conditions stipulate air monitoring is required to be carried out at the locations, at the frequency and using the test methods as set out in the tables below.

This report sets out the results of continuous monitoring summarized on a monthly basis. A separate report is issued for quarterly monitoring.

This report is prepared in accordance with the *Requirements for Publishing Pollution Monitoring Data* (EPA, October, 2013) (**Publication Requirements**).

AIR MONITORING LOCATIONS

Point	Location	Monitoring Frequency #			
1	Exhaust Stack 1 on Compression Engine 1	Continuous			

[#] Monitoring is only undertaken when the compression engine is running.

AIR MONITORING TEST METHODS - POINT 1

Parameter	NSW EPA Test Method (Sampling Method)	Reference Method			
Oxides of Nitrogen	CEM-2	USEPA Performance Specification 2			
Temperature	TM-2 USEPA Method 2				
Moisture content	Method approved by EPA in writing	Calibration by reference to TM-22			
Volumetric Flow Rate	CEM-6	USEPA Performance Specification 6			
Oxygen	CEM-3	USEPA Performance Specification 3			

USEPA Method refers to the US Environmental Protection Agency 2000, Code of Federal Regulations, Title 40, Part 60, Appendix A Methods.

USEPA Performance Specification refers to the US Environmental Protection Agency 2000, Code of Federal Regulations, Title 40, Part 60, Appendix B, Performance Specifications.



Air Monitoring Results

Continuous monitoring results are based on test results obtained over a one-hour averaging period as set out in Schedule 5 of the *Protection of the Environment Operations (Clean Air) Regulation* 2010 (NSW).

						Monitoring frequency	Number of times				
Monitoring Point	Description	Pollutant	Units of measure	Oxygen correction	Sampling method	required by licence	measured during sampling period	Minimum value	Average value	Maximum value	Concentration Limit
1	Compressor Engine 1	Oxides of Nitrogen (as	Milligrams per				Compressor Engine 1 operated from 01-17				
		NO ₂ equivalent)	cubic metre	7% oxygen	CEM-2	Continuous	and 21-25 January	157	285	395	461
		Temperature	Degrees Celsius		TM-2	Continuous	2019.	325	352	364	Not applicable
		Moisture	Percent		Method approved by EPA	Continuous	See Note 1.	7.4	8.4	11.2	Not applicable
		Volumetric flow rate	Cubic metres per second		CEM-6	Continuous		2.6	2.9	3.0	Not applicable
		Oxygen	Percent		CEM-3	Continuous		10.5	11.3	12.9	Not applicable



Notes:

 In accordance with Section 3.4.1 of the EPA Publication Requirements, the following data points have not been included for Monitoring Point 1 (Compressor #1 exhaust stack) as AGL knows that the data has been unable to be collected or is incorrect.

Date	Approximate total hours	Pollutant	Justification
02 January 2019	1	Moisture	Data unable to be collected due to light levels stabilising.
02 January 2019	2	Oxides of Nitrogen	Data unable to be collected due to light levels stabilising.
14 January 2019	1	Oxides of Nitrogen, Moisture, Temperature, Volumetric flowrate	Data unable to be collected due to light levels stabilising.
15 January 2019	2	Oxides of Nitrogen, Moisture	Data unable to be collected due to CEMS maintenance.
15 January 2019	1	Oxygen	Data unable to be collected due to CEMS maintenance.
21 January 2019	1	Moisture	Data unable to be collected due to light levels stabilising.