

AGL UPSTREAM INVESTMENTS PTY LTD ROSALIND PARK GAS PLANT Monthly Continuous Air Monitoring Report

Reporting Period: March 2019

AGL Upstream Investments Pty Ltd ABN 58 115 063 744 Locked Bag 3013, Australia Square, NSW 1215 200 George Street, Sydney NSW 2000 Telephone: 02 9921 2999 Facsimile: 02 9921 2474 Complaints Line (24 hours): 1800 039 600



Foreword				
PREMISES	Rosalind Park Gas Plant			
	Lot 35 Medhurst Road			
	GILEAD NSW 2560			
LICENCE DETAILS	Environment Protection Licence 12003			
LICENCEE	AGL Upstream Investments Pty Limited			
LICENCEE'S ADDRESS	Locked Bag 3013, Australia Square, NSW 1215			
REPORTING PERIOD	01 March 2019 to 31 March 2019			
DATE of MONITORING	Continuous			
OBTAINED DATA DATE	05 April 2019			
REPORT DATE	12 April 2019			
REPORT PREPARED BY	Aaron Clifton			
	Environment Business Partner			

SUMMARY OF ACTIVITY

Rosalind Park Gas Plant, located approximately 60km south west of Sydney, is a natural gas processing and treatment plant, used to process coal seam natural gas from the Camden Gas Project.

Produced natural gas is cleaned, dehydrated, compressed and odourised before being measured and transported by pipeline about 500 metres into the nearby Moomba to Sydney Natural Gas Pipeline. The premises are covered by Environment Protection Licence 12003 which includes all gas wells, gas gathering, reticulation systems, trunk lines and associated effluent storage areas and work areas of the Camden Gas Project.



This Monitoring Report relates to those air monitoring activities specified in Part 5, Monitoring and Recording Conditions, of Environment Protection Licence (**EPL**) 12003. The Licence conditions stipulate air monitoring is required to be carried out at the locations, at the frequency and using the test methods as set out in the tables below.

This report sets out the results of continuous monitoring summarized on a monthly basis. A separate report is issued for quarterly monitoring.

This report is prepared in accordance with the *Requirements for Publishing Pollution Monitoring Data* (EPA, October, 2013) (**Publication Requirements**).

AIR MONITORING LOCATIONS

Ρ	Point	Location	Monitoring Frequency [#]
1		Exhaust Stack 1 on Compression Engine 1	Continuous

Monitoring is only undertaken when the compression engine is running.

AIR MONITORING TEST METHODS – POINT 1

Parameter	NSW EPA Test Method (Sampling Method)	Reference Method		
Oxides of Nitrogen	CEM-2	USEPA Performance Specification 2		
Temperature	TM-2	USEPA Method 2		
Moisture content	Method approved by EPA in writing	Calibration by reference to TM-22		
Volumetric Flow Rate	CEM-6	USEPA Performance Specification 6		
Oxygen	CEM-3	USEPA Performance Specification 3		

USEPA Method refers to the US Environmental Protection Agency 2000, Code of Federal Regulations, Title 40, Part 60, Appendix A Methods.

USEPA Performance Specification refers to the US Environmental Protection Agency 2000, Code of Federal Regulations, Title 40, Part 60, Appendix B, Performance Specifications.



Air Monitoring Results

Continuous monitoring results are based on test results obtained over a one-hour averaging period as set out in Schedule 5 of the *Protection of the Environment Operations (Clean Air) Regulation* 2010 (NSW).

Monitoring Point	Description	Pollutant	Units of measure	Oxygen correction	Sampling method	Monitoring frequency required by licence	Number of times measured during sampling period	Minimum value	Average value	Maximum value	Concentration Limit
1	Compressor Engine 1	Oxides of Nitrogen (as NO ₂ equivalent)	Milligrams per cubic metre	7% oxygen	CEM-2	Continuous	Compressor Engine 1 operated from 1-14, 19-21 and 25-31	265	322	426	461
		Temperature	Degrees Celsius		TM-2	Continuous	March 2019.	336	348	357	Not applicable
		Moisture	Percent		Method approved by EPA	Continuous	See Note 1.	4.7	7.2	9.3	Not applicable
		Volumetric flow rate	Cubic metres per second		CEM-6	Continuous		2.9	2.9	3.0	Not applicable
		Oxygen	Percent		CEM-3	Continuous		10.9	11.2	11.5	Not applicable



Notes:

 In accordance with Section 3.4.1 of the EPA Publication Requirements, the following data points have not been included for Monitoring Point 1 (Compressor #1 exhaust stack) as AGL knows that the data has been unable to be collected or is incorrect.

Date	Approximate total hours	Pollutant	Justification				
01 March 2019	1	Oxides of Nitrogen, Moisture, Temperature, Volumetric flowrate	Data unable to be collected due to light levels stabilising.				
11 March 2019	1	Temperature, Volumetric flowrate	Data unable to be collected due to light levels stabilising.				
12 March 2019	1	Oxides of Nitrogen	Data unable to be collected due to CEMS maintenance.				
12 March 2019	5	Oxides of Nitrogen, Moisture, Temperature, Volumetric flowrate	Data unable to be collected due to CEMS maintenance.				
12 March 2019	1	Temperature, Volumetric flowrate	Data unable to be collected due to CEMS maintenance.				
19 March 2019	12	Oxides of Nitrogen, Moisture	Data unable to be collected due to instrument fault.				
20 March 2019	5	Oxides of Nitrogen, Moisture	Data unable to be collected due to CEMS maintenance.				
20 March 2019	1	Moisture	Data unable to be collected due to light levels stabilising.				
25 March 2019	1	Oxides of Nitrogen, Moisture, Temperature, Volumetric flowrate	Data unable to be collected due to CEMS maintenance.				
25-31 March 2019	145	Volumetric flowrate	Data unable to be collected due to instrument fault.				