

AGL UPSTREAM INVESTMENTS PTY LTD ROSALIND PARK GAS PLANT Air Monitoring Report

Reporting Period: April 2012

AGL Upstream Investments Pty Ltd
ABN 58 115 063 744
Locked Bag 1837, St Leonards NSW 2065
Level 22, 101 Miller Street, North Sydney NSW 2060
Telephone: 02 9921 2999 Facsimile: 02 9921 2474
Complaints Line (24 hours) 02 9963 1318



Foreword

PREMISES Rosalind Park Gas Plant

Lot 35 Medhurst Road GILEAD NSW 2560

LICENCE DETAILS Environment Protection Licence 12003

LICENCEE AGL Upstream Investments Pty Limited

LICENCEE'S ADDRESS Locked Bag 1837, North Sydney, NSW 2060

REPORTING PERIOD 31 March to 30 April 2012

REPORT DATE 19 July 2012

REPORT PREPARED BY Aaron Clifton

Environmental Manager

SUMMARY OF ACTIVITY

Rosalind Park Gas Plant, located approximately 60km south west of Sydney, is a natural gas processing and treatment plant, used to process coal seam natural gas from the Camden Gas Project.

Produced natural gas is cleaned, dehydrated, compressed and odourised before being measured and transported by pipeline about 500 metres into the nearby Moomba to Sydney Natural Gas Pipeline. The premises covered by this Environment Protection Licence also includes all gas wells, gas gathering, reticulation systems, trunk lines and associated effluent storage areas and work areas of the Camden Gas Project.

This Monitoring Report relates to those air monitoring activities specified in Part 5, Monitoring and Recording Conditions, of the Environment Protection Licence. The Licence conditions stipulate air monitoring is required to be carried out at the locations, at the frequency and using the test methods as set out in the tables below.

This report sets out the results of continuous monitoring summarized on a monthly basis. A separate report is issued for quarterly monitoring.



AIR MONITORING LOCATIONS

Point	Location	Monitoring Frequency			
1	Exhaust Stack 1 on Compression Engine 1	Continuous			
2	Exhaust Stack 2 on Compression Engine 2	Continuous			
3	Exhaust Stack 3 on Compression Engine 3	Continuous			

AIR MONITORING TEST METHODS

Parameter	NSW EPA Test Method (Sampling Method)	Reference Method			
Oxides of Nitrogen	CEM-2	USEPA Performance Specification 2			
Temperature	TM-2	USEPA Method 2			
Moisture content	TM-22	USEPA Method 4			
Volumetric Flow Rate	CEM-6	USEPA Performance Specification 6			
Oxygen	CEM-3	USEPA Performance Specification 3			

USEPA Method refers to the US Environmental Protection Agency 2000, Code of Federal Regulations, Title 40, Part 60, Appendix A Methods.

USEPA Performance Specification refers to the US Environmental Protection Agency 2000, Code of Federal Regulations, Title 40, Part 60, Appendix B, Performance Specifications.



Air Monitoring Results

Monitoring Point	Description	Pollutant	Units of measure	Oxygen correction	Sampling method	Monitoring frequency required by licence	Number of times measured during sampling period	Minimum value	Average value	Maximum value	Concentration limit
1	Compressor Engine 1	Oxides of Nitrogen	milligrams per cubic metre	7% oxygen	CEM-2	Continuous	Equipment downtime (due to equipment breakdown)				461
	Liigille 1	Temperature	degrees Celsius	7 % Oxygen	TM-2	Continuous					401
		Moisture	percent		TM-22	Continuous					
		Volumetric flow rate	cubic metres per second		CEM-6	Continuous					
		Oxygen	percent		CEM-3	Continuous					
2	Compressor Engine 2	Oxides of Nitrogen	milligrams per cubic metre	7% oxygen	CEM-2	Continuous	Equipment downtime (due to equipment breakdown)				461
		Temperature	degrees Celsius		TM-2	Continuous					
		Moisture	percent		TM-22	Continuous					
		Volumetric flow rate	cubic metres per second		CEM-6	Continuous					
		Oxygen	percent		CEM-3	Continuous					
3	Compressor Engine 3	Oxides of Nitrogen	milligrams per cubic metre	7% oxygen	CEM-2	Continuous	Equipment downtime (due to equipment breakdown)				461
		Temperature	degrees Celsius		TM-2	Continuous					
		Moisture	percent		TM-22	Continuous					
		Volumetric flow rate	cubic metres per second		CEM-6	Continuous					
		Oxygen	percent		CEM-3	Continuous					

Note: Continuous monitoring results are based on test results obtained over a one-hour averaging period as set out in Schedule 5 of the *Protection* of the Environment Operations (Clean Air) Regulation 2010 (NSW).